

A COMPOSITION AND METHOD FOR CLEANING SURFACES

Reference to Pending Applications

This application is a continuation-in-part of United States Patent Application No. 09/324,383 filed on June 2, 1999 and entitled A COMPOSITION AND METHOD FOR CLEANING DRINK WATER TANKS.

Reference to Microfiche Appendix

This application is not referenced in any microfiche appendix.

Background of the Invention

This invention relates generally to the cleaning of surfaces having deposits and more particularly, to the removal of particular types of deposits formed along these surfaces. Such surfaces are located along internal surfaces of drink water tanks, supply water wells, water filter systems, and distributor water lines.

Typically these surfaces are constantly being exposed to water and air. For example, the water level of a drink water tank rises and falls with demand. This constant change between water exposure and air exposure cause a biological film, such as algae and microorganisms, along with incrustations such as calcium, iron and manganese to form deposits along these surfaces.

Cleaning these deposits from these surfaces has been the subject of a number of prior art compositions. U.S. Patent No. 4,199,469 issued to Waltzer on April 22, 1980 discloses a composition and method for cleaning drink water tanks. This composition utilizes a group of acids (ascorbic, formic, phosphoric, citric and hydrochloric).

1

CERTIFICATE OF EXPRESS MAILING UNDER 37 CFR 1.10	
I hereby certify that this document and any document referred to as being attached therein is being deposited with the U.S. Postal Service in an envelope as "Express Mail Post Office to Addressee", Mailing Label No. EL502556656US, addressed to: Box PATENT APPLICATION, Assistant Commissioner for Patents, Washington, D.C. 20231, June 1, 2000.	
LUZ C. LOPEZ	<i>Luz C. Lopez</i>
(Name of Person Mailing Paper)	(Signature of Person Mailing Paper)

Once the surfaces have been cleaned by a cleaning composition, a disinfectant is normally applied. This additional process adds time and resources to the overall cleaning process. Given the number of constituents the composition is complicated and confusing. Therefore, there exists a need for a more simple composition in order to clean surfaces having deposits contained thereon.

10012003-102001

Brief Summary of the Invention

10012003-10224
15
5 This invention relates generally to the cleaning of surfaces having deposits and more particularly, to the removal of particular types of deposits formed along these surfaces. Such surfaces can be located along internal surfaces of drink water tanks, supply water wells, water filter systems, and distributor water lines.

The present invention is directed, generally, to a composition for such surfaces. The composition includes in combination a cleaning solution portion and a disinfectant portion.

The cleaning solution portion generally includes hydrochloric acid and/or phosphoric acid in combination with inhibitors, dyes and water. The disinfectant is a standard disinfectant, such as but not limited to hydrogen peroxide or peracetic acid.

The composition is applied to the surfaces having deposits of biological film, such as but not limited to algae and microorganisms and/or incrustations such as but not limited to calcium, iron and manganese thereon. The solution loosens the adhesion between the deposits and the surface at which time the composition and deposits are rinsed away. Further, the biological film is reliably eliminated.

It is a primary object of the invention to provide a composition and method for cleaning surfaces that avoids the problems mentioned above.

Another object of the invention is to provide a solution for cleaning and disinfecting such surfaces.

20 Other objects and further scope of the applicability of the present invention will become apparent from the detailed description to follow wherein like parts are designated by like reference numerals.

Detailed Description of the Preferred Embodiments

This invention relates generally to the cleaning of surfaces having deposits and more particularly, to the removal of particular types of deposits formed along these surfaces. Such surfaces are located along internal surfaces of drink water tanks, supply water wells, water filter systems, and distributor water lines.

The present invention is directed, generally, to a composition for cleaning such surfaces. The composition includes in combination a cleaning solution portion and a disinfectant portion. The composition is applied to drink water tank surfaces have deposits formed thereon.

The cleaning solution portion generally includes hydrochloric acid and/or phosphoric acid in combination with inhibitors, dyes and water. The disinfectant is a standard disinfectant, such as but not limited to hydrogen peroxide or peracidic acid.

The preferred embodiment of the present invention is directed toward the cleaning of surfaces specifically for the removal of deposits which have formed thereon and providing a disinfectant in combination.

With respect to the cleaning solution portion, one basic formula is:

Ingredients	Weight/Percentage (Preferred)
Sulfamic	2.0 %
Citric Acid	10.0 %
Glycolic Acid	14.6 %
Phosphoric	12.9 %
Rodine	1.8 %
Hydrochloric Acid	10.0 %

Ingredients	Weight Percentage (Preferred)
Sulfamic	2.0 %
Inhibitors	0.4 %
Dyes	0.009 %
Water	Balance

Additional formulas include:

Ingredients	Weight Percentage (Preferred)
Hydrochloric Acid	9.0 %
Citric Acid	0.4 %
Phosphoric Acid	2.0 %
Triethylene glycol	0.50 %
Water	Balance

II.

Ingredients	Weight Percentage (Range)
Hydrochloric Acid	5.0 - 20.0 %
Phosphoric Acid	5.0 - 20.0 %
Inhibitor	0.05 - 1.0 %
Isopropanol	0.1 - 1.0 %
Water	Balance

III.

Ingredients	Weight Percentage (Range)
Phosphoric Acid	5.0 - 20.0 %
Inhibitor	0.05 - 1.0 %
Isopropanol	0.1 - 1.0 %
Water	Balance

IV.

Ingredients	Weight Percentage (Range)
Hydrochloric Acid	5.0 - 20.0 %
Inhibitor	0.05 - 1.0 %
Isopropanol	0.1 - 1.0 %
Water	Balance

V.

Ingredients	Range (Weight Percentage)	
	Broad	Preferred
Amidosulfamic Acid	4 - 30 %	10 %
Nitrilotriacetic Acid	0.1 - 0.2 %	0.15 %
Isopropanol	0.1 - 0.5 %	0.3 %
Water	Balance	Balance

A disinfectant portion is added to cleaning solution in order to provide a disinfecting capability. The disinfectant portion is a standard disinfectant, such as but not limited to hydrogen

peroxide or peracidic acid. The range of the disinfectant portion is 0.1 to 10.0 % by volume of the entire composition.

The composition of the preferred embodiment of the present invention is applied to the surface where deposits have formed. These deposits comprise the combination of a biological film, such as algae and microorganisms, with sediments, such as calcium, iron and/or manganese. The composition of the preferred embodiment loosens the adhesive bond between the deposits and the wall surface allowing for the removal thereof. The composition is then rinsed away along with the loosened deposits as well as any remaining biological film.

It is to be understood that the above description is illustrative only and not limiting of the disclosed invention.

The claims and the specification describe the invention presented and the terms that are employed in the claims draw their meaning from the use of such terms in the specification. The same terms employed in the prior art may be broader in meaning than specifically employed herein. Whenever there is a question between the broader definition of such terms used in the prior art and the more specific use of the terms herein, the more specific meaning is meant.

While the invention has been described with a certain degree of particularity, it is manifest that many changes may be made in the details of construction and the arrangement of components without departing from the spirit and scope of this disclosure. It is understood that the invention is not limited to the embodiments set forth herein for purposes of exemplification, but is to be limited only by the scope of the attached claim or claims, including the full range of equivalency to which each element thereof is entitled.